



Highlights

- ✔ **Price for Performance** RISC processor hardware architecture
- ✔ **Flexible** able to run a range of applications
- ✔ **Manageable** The Chip PC *Xcalibur XP* management software
- ✔ **Secured** against viruses, worms, and requires no security patches
- ✔ **Accessible** Windows CE.NET, IE5.5, ICA6.3, RDP5.1
- ✔ **Compact** Weighting as little as 180gm (6.35 oz) and easily appended, the units are quick to handle, ship, store, and install.
- ✔ **Power saver** 3.5W at full working mode

Xtreme PC EL-4610

Xtreme PC EL 4610 is the smartest and smallest thin client on the market.

With innovative hardware design, low power consumption, and management software, these slim, compact, and easily appended units truly form the Thin Client family of choice.

Xtreme PC EL 4610 offers users in various environments a whole array of Office applications, and integrated local browser IE 5.5.

Supported by **Xcalibur XP** management software, the **Xtreme PC EL 4610** is the most manageable thin client solution, either remotely or locally.

Xcalibur XP management software is a web-based management – all you need is a standard web browser to manage the devices remotely.



EL-4610 Hardware Specification Table

CPU	Super-H RISC processor, 250 MIPS
Memory	64 MB DOC
Mass Storage	32 MB SDRAM on board
Video Memory	128-bit 2D graphics acceleration engine with separate 2MB display memory SDRAM
Display Support	<ul style="list-style-type: none"> • Color VGA/SVGA/XGA, BD-15HD female connector • Resolution up to 1024x768 pixels; Color up to 16M ; Refresh rate: up to 85 Hz • Supports VESA standard CRT & LCD
Input/Output	<ul style="list-style-type: none"> • VGA –type video (DB-15) • 1 Serial port RS-232, 1 Parallel port, 2 PS/2 ports for mouse and keyboard
Status Lights	<ul style="list-style-type: none"> • Power ON - Self-Test passed (Green), Power STBY - Self-Test failed (Red), LAN Link - Activity (Green/Amber)
Audio Support	<ul style="list-style-type: none"> • System sound – Internal 1W amplifier & speaker/Audio out – 3.5 mm (1/8 inch) • Software volume/mute control
Network	<ul style="list-style-type: none"> • 10/100 Fast Ethernet, twisted pair (RJ-45) • TCP/IP with DNS and DHCP • Point-to-Point Protocol (PPP) • SNMP Support - allows remote configuration of device settings • Compliant with IEEE 802.3 LAN & 802.3U-LAN
Power	<ul style="list-style-type: none"> • Device input: 5V DC 2.4A max. • Work Mode - 5W , Sleep Mode - 0.35W • Wall-mount power supply input: Universal 90 – 240V AC, 50-60 Hz (included)
Operating System	<ul style="list-style-type: none"> • Microsoft Windows CE.NET with IE 5.5
Protocols Supported	<ul style="list-style-type: none"> • ICA 6.3 • RDP 5.1
Management	<ul style="list-style-type: none"> • Xcalibur XP client (optional)
Compliant Servers	<ul style="list-style-type: none"> • Microsoft NT/XP/2000/2003 • Citrix WinFrame, Metaframe
Physical Characteristics	<ul style="list-style-type: none"> • Dimensions: 80(W)x158(D)x34(H) mm / 3.15(W)x6.22(D)x1.34(H) inch • Device weight: 180 gr. (6 oz.) • Shipping Weight: Per single pack - 0.65 Kg. (1.43 lbs.) ; Per ten pack - 5.85 Kg. (12.9 lbs.)
Mounting	<ul style="list-style-type: none"> • Special base attachment • VESA (optional, see Accessories) • Anti Theft Lock (optional, see Accessories)
Enclosure Color	Midnight Gray and Silver
Environmental	<ul style="list-style-type: none"> • Temperature range: Operating - 0°C to 40°C (32°F to 104°F); Storage - 0°C to 60°C (32°F to 140°F) • Humidity: Operating - 20 to 80% non condensing; Storage – 10 to 90% non condensing • Altitude: 0 to 20,000 ft
Regulatory Compliance	<ul style="list-style-type: none"> • Safety: UL/cUL60950,EN60 950 • EMI/EMC: FCC Class B, CE Mark, EN55022B, VCCI • EPA ENERGY STAR
Accessories	Visit our site at www.chippc.com for an updated list
Warranty	1 year Warranty

Chip PC HQ

Tel: +972 (4) 8501121
e-mail: info@chippc.com

Chip PC Inc US

Tel: +1-866-674-1678
e-mail: info.us@chippc.com

Chip PC UK

Tel: +44 (0) 870 606 1007
e-mail: info@chippc.co.uk

- Monitor, Keyboard and Mouse (not included)
- Supported firmware image 4.0.5, Xcalibur licenses (optional)
- Specifications are subjected to change without prior notice
- © Chip PC Technologies, all rights reserved.
- Images for demonstration purposes only | 11.2006