



ChipZed,

Zero Client for Citrix & RDP

Hardware



Specification		
Processor	CPU	ARM Cortex A9 1.0GHz
Memory	RAM / Storage	512MB Flash/ 512MB DDR3 RAM (Centerm Linux)
I/O Peripheral Support	Serial	None
	Parallel	None
	USB 2.0	X5 (Front x1, back x4)
	DVI-I	X1
	PS/2 Keyboard & Mouse	NONE
Networking	LAN	x1 (10/100/1000 Base-T Fast Ethernet, RJ-45)
Display Support		DVI-I -->DVI-D+VGA
	Resolution	up to 1920x1200 @60Hz, 24 bit true color
Audio	Line-out & Mic-in	
Physical Characteristics:	Dimension/Weight	Terminal Box: 156.4mm(L) x 130mm(W) x 37mm(H)/0.44kg Packing: Single Box: 325mm(L) x 220mm(W) x 85mm(H)/1.00kg
	Mountings	VESA Bracket VESA Mounting Kit
Power	Adapter	5V/3A DC Power Worldwide auto-sensing 100-240V AC, 50/60 Hz
	Consumption	Maximum 6 Watts
Environment	Operation Temperature	0°C – 40°C
	Relative Humidity	30% to 90% non-condensing

Software

Firmware Features (System dependant)	
Zero	Citrix xenapp client installed , Rdesktop
Server OS Support	Citrix XenApp / Citrix Presentation Server / RDP
Set-up and configuration	Boot from local Flash User interface language: U.S English, Keyboard Language support: U.S. English standard,
Management	Remote management, configuration, and upgrade through Centerm Management software